



Appendino

Finitura bianco: cod. APPB
Finitura cromo: cod. APPC

Towel peg

White finishing: code APPB
Chromium plated finishing: code APPC



Stendino

Larghezza 400 mm
Finitura bianco: cod. STEB4
Finitura cromo: cod. STEC4

Towel rail

Width 400 mm
White finishing: code STEB4
Chromium plated finishing: code STEC4

Larghezza 500 mm

Finitura bianco: cod. STEB5
Finitura cromo: cod. STEC5

Width 500 mm

White finishing: code STEB5
Chromium plated finishing: code STEC5



Piedino di sostegno

Cod. PIED
L'altezza del supporto, grazie alla regolazione verticale, può variare da 180 mm a 190 mm.

Support foot

Code PIED
The support height, by the vertical adjustment, can vary from 180 mm to 190 mm.



Piedino di sostegno

Cod. PIEG
Piedino di sostegno per termoarredo modello Giorgione.
Altezza del supporto 100 mm.

Support foot

Code PIEG
Support foot for radiator model Giorgione.
Height support 100 mm.



Raccordo a T

Finitura bianco: cod. RATB
Finitura cromo: cod. RATC

T connection

White finishing: code RATB
Chromium plated finishing: code RATC



Resistenza elettrica

Resistenza elettrica, classe 1, indice di protezione IP64, 230 V. Completo di cavo di alimentazione e spina Schuko.
Finitura bianco: cod. REB
Finitura cromo: cod. REC

Immersion heater

Immersion heater, class 1, IP64 protection rating, 230 V. Cable and die-cast Schuko are included.
White finishing: code REB
Chromium plated finishing: code REC



Resistenza elettrica con interruttore on/off

Resistenza elettrica con interruttore on/off, classe 1, indice di protezione IP64, 230 V. Completo di cavo di alimentazione e spina Schuko. Dimensioni 103x35x39 mm (HxLxP). Permette di accendere e spegnere l'apparecchio attraverso l'apposito pulsante.
Finitura bianco: cod. INB
Finitura cromo: cod. INC

Immersion heater with on/off switch

Immersion heater with on/off switch, class 1, IP64 protection rating, 230 V. Cable and die-cast Schuko are included. Dimensions 103x35x39 mm (HxWxD). By the switch it is possible to turn on and off the apparatus.
White finishing: code INB
Chromium plated finishing: code INC



Termostato elettronico analogico

Resistenza elettrica con termostato elettronico analogico, classe 1, indice di protezione IP64, 230 V. Completo di cavo di alimentazione e spina Schuko. Dimensioni 73x113x40 mm (HxLxP). Permette la regolazione manuale della temperatura attraverso l'apposita manopola termostato.
Finitura bianco: cod. TAB
Finitura cromo: cod. TAC

Analogical electronic thermostat

Immersion heater with analogical electronic thermostat, class 1, IP64 protection rating, 230 V. Cable and die-cast Schuko are included. Dimensions 73x113x40 mm (HxWxD). By the thermostat knob it is possible the manual regulation of the temperature.
White finishing: code TAB
Chromium plated finishing: code TAC



Cronotermostato digitale LCD

Resistenza elettrica con cronotermostato digitale LCD, classe 1, indice di protezione IP64, 230 V. Completo di cavo di alimentazione e spina Schuko. Dimensioni 76x131x42 mm (HxLxP). Permette la programmazione giornaliera e settimanale personalizzata della temperatura.
Finitura bianco: cod. CDB
Finitura cromo: cod. CDC

LCD digital crono-thermostat

Immersion heater with LCD digital crono-thermostat, class 1, IP64 protection rating, 230 V. Cable and die-cast Schuko are included. Dimensions 76x131x42 mm (HxWxD). Permit the daily and weekly personalized programming of the temperature.
White finishing: code CDB
Chromium plated finishing: code CDC