



### Appendino

Finitura bianco: cod. APPB  
Finitura cromo: cod. APPC

### Towel peg

White finishing: code APPB  
Chromium plated finishing: code APPC



### Stendino

Larghezza 400 mm  
Finitura bianco: cod. STEB4  
Finitura cromo: cod. STEC4

### Towel rail

Width 400 mm  
White finishing: code STEB4  
Chromium plated finishing: code STEC4

Larghezza 500 mm

Finitura bianco: cod. STEB5  
Finitura cromo: cod. STEC5

Width 500 mm

White finishing: code STEB5  
Chromium plated finishing: code STEC5



### Piedino di sostegno

Cod. PIED  
L'altezza del supporto, grazie alla regolazione verticale, può variare da 180 mm a 190 mm.

### Support foot

Code PIED  
The support height, by the vertical adjustment, can vary from 180 mm to 190 mm.



### Piedino di sostegno

Cod. PIEG  
Piedino di sostegno per termoarredo modello Giorgione.  
Altezza del supporto 100 mm.

### Support foot

Code PIEG  
Support foot for radiator model Giorgione.  
Height support 100 mm.



### Raccordo a T

Finitura bianco: cod. RATB  
Finitura cromo: cod. RATC

### T connection

White finishing: code RATB  
Chromium plated finishing: code RATC



#### Resistenza elettrica

Resistenza elettrica, classe 1, indice di protezione IP64, 230 V. Completo di cavo di alimentazione e spina Schuko.  
Finitura bianco: cod. REB  
Finitura cromo: cod. REC

#### Immersion heater

Immersion heater, class 1, IP64 protection rating, 230 V. Cable and die-cast Schuko are included.  
White finishing: code REB  
Chromium plated finishing: code REC



#### Resistenza elettrica con interruttore on/off

Resistenza elettrica con interruttore on/off, classe 1, indice di protezione IP64, 230 V. Completo di cavo di alimentazione e spina Schuko. Dimensioni 103x35x39 mm (HxLxP). Permette di accendere e spegnere l'apparecchio attraverso l'apposito pulsante.  
Finitura bianco: cod. INB  
Finitura cromo: cod. INC

#### Immersion heater with on/off switch

Immersion heater with on/off switch, class 1, IP64 protection rating, 230 V. Cable and die-cast Schuko are included. Dimensions 103x35x39 mm (HxWxD). By the switch it is possible to turn on and off the apparatus.  
White finishing: code INB  
Chromium plated finishing: code INC



#### Termostato elettronico analogico

Resistenza elettrica con termostato elettronico analogico, classe 1, indice di protezione IP64, 230 V. Completo di cavo di alimentazione e spina Schuko. Dimensioni 73x113x40 mm (HxLxP). Permette la regolazione manuale della temperatura attraverso l'apposita manopola termostato.  
Finitura bianco: cod. TAB  
Finitura cromo: cod. TAC

#### Analogical electronic thermostat

Immersion heater with analogical electronic thermostat, class 1, IP64 protection rating, 230 V. Cable and die-cast Schuko are included. Dimensions 73x113x40 mm (HxWxD). By the thermostat knob it is possible the manual regulation of the temperature.  
White finishing: code TAB  
Chromium plated finishing: code TAC



#### Cronotermostato digitale LCD

Resistenza elettrica con cronotermostato digitale LCD, classe 1, indice di protezione IP64, 230 V. Completo di cavo di alimentazione e spina Schuko. Dimensioni 76x131x42 mm (HxLxP). Permette la programmazione giornaliera e settimanale personalizzata della temperatura.  
Finitura bianco: cod. CDB  
Finitura cromo: cod. CDC

#### LCD digital crono-thermostat

Immersion heater with LCD digital crono-thermostat, class 1, IP64 protection rating, 230 V. Cable and die-cast Schuko are included. Dimensions 76x131x42 mm (HxWxD). Permit the daily and weekly personalized programming of the temperature.  
White finishing: code CDB  
Chromium plated finishing: code CDC